

SOFTLINE 70

Frame width 70 mm

The universal window frame depth of 70 mm allows installation on practically any wall.

Thermal insulation

The heat transfer coefficient of the product can be reached up to $U_w = 0.9 \text{ W/m}^2\text{K}$

Sealing gaskets

Fixation of two exchangeable sealing gaskets between the frame and the hinged part

Glazing

24 - 42 mm glass units are used.

Class A requirements

The wall thicknesses of the profile meet the strict requirements of class A as well as class B.

Reinforcement profiles

"Closed" reinforcement profiles used in the frame and crossbar increase the static characteristics of the products.

Classic design

The elegant design of the outer contour of the profile echoes the classic SOFTLINE system.

Fittings

The reliable and elegant fittings of the MACO system are used.

Additionally

Air vents can be installed in a glass package or is milled. Vertical mounting is also possible "Soviet" airlines.

Outdoor door

Exterior doors are available with 1-bolt, 4-roller or 3-bolt automatic lock.



The VEKA color palette



Colors

golden oak	walnut	mahogany	dark oak	brown	siena rosso	siena noce	winchester
douglas	stripe-douglas	mountain pine	oregon III	light oak	rustic oak	shogun AC	shogun AD
shogun AF	macore	rosewood	white	papyrus white	creme white	light ivory	zinc yellow
light grey	agate grey	silver grey	silver grey smooth	basalt grey	basalt grey smooth	anthrazite grey	anthrazite grey smooth
slate grey	slate grey smooth	quarz grey	quarz grey smooth	alux graualuminium	brillant blue	cobalt blue	steel blue
monument blue	emerald green	mossgreen	fir green	monument green	carmine red	ruby red	brown red
wine red	black brown	jet black	aluminium brushed	metbrush messing	crown platin	quarz platin	earl platin